

PRODUCT DATA SHEET

Casco® LimTvätt

Cleaning and removing residues of contact and dispersion-based adhesives.

DESCRIPTION

Also suitable for mixing in cleaning water to remove adhesive pressed out when installing wall or flooring material.

Non-water-based content.

CHARACTERISTICS / ADVANTAGES

- Water soluble
- Removes various adhesive

USES

Intended for removing residue when gluing PVC, linoleum and polyolefin mats to floors, and PVC sheeting on walls.

PRODUCT INFORMATION

Composition	Mixture of solvents and tensides
Active content	Isopropyl alcohol, acetone, ethanol, distillates, hydrotreated light
Packaging	1 L
Shelf life	12 months from production date (s. packaging) in sealed packaging.
Storage conditions	Store in a cool, frost-free place.
Appearance and colour	Clear, thin liquid
Density	800 kg/m ³
Flash point	< 23°C

APPLICATION INFORMATION

Substrate temperature	+15°C to +25°C
-----------------------	----------------

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

EQUIPMENT

Cloth

SUBSTRATE QUALITY / PRE-TREATMENT

Casco® LimTvätt is not suitable for sensitive surfaces such as those painted with alkyd or oil paints, untreated wood, etc.

We recommend performing a preliminary test.

MIXING

Casco® LimTvätt can be mixed with water to loosen adhesive residues. Mix 1–2 parts Casco® LimTvätt with 10 parts water.

APPLICATION

Casco® LimTvätt is intended for removing adhesive residue and stains that have dried. When removing these, use Casco® LimTvätt in concentrated form.

Apply Casco® LimTvätt. Leave to work for a few minutes. Rub with a cloth or, in tougher cases, a scouring pad. Wipe up the dissolved adhesive residue. Clean with water and wipe down with a clean cloth.

It may sometimes be necessary to leave Casco® LimTvätt to work for 10–15 minutes.

NB! If the product is left to work for too long, it may damage the surface of delicate materials.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB

Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu



PRODUCT DATA SHEET

Casco® LimTvätt
November 2022, Version 01.01
020816210010000019

CascoLimTvtt-en-SECASCO-(11-2022)-1-1.pdf

