

PRODUCT DATA SHEET

CascoLin Extra

FAST ADHESIVE ESPECIALLY DEVELOPED FOR LINOLEUM.

DESCRIPTION

Fast adhesive especially developed for linoleum. Suitable for needlefelt, vinyl with backing of polyester felt, acoustic backing and linoleum with polyurethane surface.

USES

- Linoleum
- Linoleum with polyurethane surface
- Needlefelt
- Vinyl with backing of polyester felt
- Vinyl with acoustic backing linoleum with polyurethane surface

CHARACTERISTICS / ADVANTAGES

- Fast bonding
- Very good tack, gives good initial bonding
- No risk of expansion of coverings
- Contains no APEO
- Suitable for absorbent subfloor
- Suitable for floor heating
- Suitable for castor wheels

PRODUCT INFORMATION

Composition	Copolymer of acrylic dispersion
Packaging	10 liter bucket
Colour	Light yellow
Shelf life	12 months if stored in minimum +10 °C in well closed packages.
Storage conditions	May not be exposed to temperatures below 0 °C and above +30 °C.
Density	Appr. 1400 kg/m ³
Consistency	Thixotropic
Solid content by weight	Appr. 80 %
Viscosity	Appr. 55 000 mPa.s, Brookfield RVT, sp 6, 10 rpm, 25 °C

APPLICATION INFORMATION

Consumption	1 liter / 3-3,5 m ²
Ambient Air Temperature	+18 °C to +23 °C and 20–70 % RH. The climate must be maintained for at least 96 h (4d) for optimal result.
Application Time	absorbent subfloor, appr. 0–20 min.

Yield

Absorbent and non-absorbent subfloor
Textile: 3-3,5 m²/l
Linoleum: 3-3,5 m²/l

APPLICATION INSTRUCTIONS

When using CascoLin Extra on new produced concrete we recommend minimum 10 mm self leveling compound.

Note; For best result, linoleum shall be installed on a porous subfloor and in wet adhesive.

ON POROUS SUBFLOORS

1. Spread the adhesive with a toothed trowel. Don't use more adhesive than necessary to give a good over-wetting.
2. Install the covering at once or after a very short open time and rub thoroughly to press out all the air to achieve a good contact between the adhesive and the covering. For best result use a carpet roller.
3. Check that the whole covering area has full contact with the adhesive

ON NON-POROUS SUBFLOORS

For best result, create an absorbent subfloor by using a floor levelling compound with low shrinkage and good adhesion to the subfloor. Build up a layer of 2-3 mm. Follow the gluing instructions above "on porous subfloors".

Follow the recommendations from the linoleum manufacturer with regard to temperature and RH.

SUBSTRATE PREPARATION

Before installing the covering make sure that the subfloor is clean, even and dust free and has an adequate strength, bearing strength, dimensional stability and is permanent dry.

The moisture content in the concrete must not exceed 85 % RH and the chipboard moisture quota should be 8-12 %.

CLEANING OF EQUIPMENT

Always make sure to use suitable gloves and goggles when handling the product. Work carefully and systematically in order to avoid unnecessary spillage. In case of skin contact, wash with soap and water. In case of eye contact, rinse thoroughly with water. Clean application tools with water before the adhesive has dried. Dried adhesive is dissolved in ethanol. For further information, see Safety Data Sheet.

Sika Sverige AB

Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

APPLICATION

Toothed trowel 6121

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

CascoLinExtra-en-SECASCO-(03-2020)-1-2.pdf

PRODUCT DATA SHEET

CascoLin Extra
March 2020, Version 01.02
020512030110000004