

PRODUCT DATA SHEET

AquaProff

WALL ADHESIVE FOR WET ROOMS.



DESCRIPTION

Wall adhesive, suitable for gluing most types of plastic wall coverings with PVC layer thicker than 0.6 mm. Suitable for horizontal application of wall coverings.

USES

- For wet rooms
- For plastic wall coverings with PVC layer thicker than 0.6 mm
- For horizontal application of wall coverings

CHARACTERISTICS / ADVANTAGES

- Weldable
- For roller and brush application
- Easy to apply
- Minimal splashing
- Contains no APEO

APPROVALS / CERTIFICATES

- EC1 Plus for very low emission

PRODUCT INFORMATION

Composition	Copolymer of acrylic dispersion
Packaging	10 liter rectangular bucket
Shelf life	12 months from production date (s. packaging) in unopened packaging. Opened packaging should be closed immediately and used up as soon as possible.
Storage conditions	May not be exposed to temperatures below +5°C and above +30°C.
Colour	Grey-white
Density	1450 kg/m ³
Solid content by mass	72 %
Viscosity	Approx. 45 000 mPa.s, Brookfield RVT, sp 6, 10 rpm, 25° C
Consistency	Thixotropic

APPLICATION INFORMATION

Yield	Material	
	Homogenius PVC	3-5 m ² /l
	PVC	3-5 m ² /l
Substrate temperature	+18°C to +23°C	
Application time	0-15 min.	

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Before installing the covering make sure that the sub-floor is clean, even and dust free and has adequate strength, bearing strength, dimensional stability and is permanently dry.

The moisture content in the concrete must not exceed 85% RH.

APPLICATION METHOD / TOOLS

Roller or brush.

APPLICATION

POROUS SUBSTRATES (like concrete, wet strong putty, particle board and gypsum plaster boards):

1. Spread the adhesive evenly on the wall with a roller. Don't apply the adhesive on larger areas than you can assemble it in 15-20 minutes. Apply the covering immediately or after a waiting time of 5 to 10 minutes.
2. Rub thoroughly to press out all the air to achieve good contact between the adhesive and the covering.
3. Check that the whole covering area has full contact with the adhesive.

Sika Sverige AB

Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

- Join the material according to the material producer's instruction.
- In case of heat re-activation, do not use more heat than necessary, especially when working with corners.
- On porous substrate, always make sure you let the walls dry for 2 days, until you use the room, after gluing the covering.

NOTE! Strong absorbent surface must be primed with primer or a mixture of AquaProff and water 1:1.

CLEANING OF EQUIPMENT

Always make sure to use suitable gloves and goggles when handling the product. Work carefully and systematically to avoid unnecessary spillage. In case of skin contact, wash with soap and water. In case of eye contact, rinse thoroughly with water. Clean application tools with water before the adhesive has dried. Dried adhesive is dissolved in ethanol.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of CASCOFE products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.CASCOFE.eu.

AquaProff-en-SECASCOFE-(04-2023)-2-1.pdf

PRODUCT DATA SHEET

AquaProff
April 2023, Version 02.01
020512030110000018