

PRODUCT DATA SHEET

Casco[®] Häftmassa

Reusable adhesive (tacky dough) for fixing light weight objects such as paper, posters, maps etc

DESCRIPTION

Reusable adhesive (tacky dough) for fixing light weight objects such as paper, posters, maps etc.

USES

Can also be used for securing loose objects such as telephones, keys, screws, ornaments etc.

CHARACTERISTICS / ADVANTAGES

- "Tacky dough" for posters, pictures, maps etc
- Reusable

SUSTAINABILITY

For the product's assessment in the different building criteria systems, see [MiljöAppen](#).

Here you will also find information about EC1, M1, link to the building product declaration, safety data sheets etc. The MiljöAppen, can also be reached by entering www.sikamiljoapp.se in your web browser.

PRODUCT INFORMATION

Composition	Polybutene and mineral filler Solvent: None
Packaging	Piece cont. 60 g
Shelf life	24 months in closed package
Storage conditions	May not be exposed to temperature below +10 °C or above +30 °C
Colour	White dough
Density	~1700 kg/m ³
Solid content by mass	Dry solids: ~100 %
Consistency	Low viscous

APPLICATION INFORMATION

Substrate temperature	Application temperature: +5 °C to +30 °C
Curing time	Non drying

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

Observe good cleanliness when working with the product.

Keep out of reach of children.

Do not empty into drains.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Joint interface must be clean, dry and free from oils, loose aggregates, laitance, release agents, waterproofing and other contaminants.

DIRECTIONS FOR USE

Ensure that surfaces to be affixed to are clean and dust free.

Pull a small piece (form a ball of the dough) of reusable adhesive from the block and press firmly to the back of the object to be affixed.

Press the object firmly onto the surface to be affixed to.

When removing reusable adhesive from paper, take extra care and remove gently to avoid tearing the paper.

NOTE: If the product is used on absorbing uncoated paper, e.g. wallpaper, permanent spots of grease stains may occur.

A pre-test is recommended.

CLEANING OF EQUIPMENT

Cleaning is best made with soap and water

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB

Domnarvsgatan 15

Box 8061

SE- 163 08 Spånga Sweden

TEL: +46 8 621 89 00

info@se.sika.com

www.casco.eu

PRODUCT DATA SHEET

Casco® Häftmassa

March 2023, Version 02.01

02051307000000054