


PRODUCT DATA SHEET

Casco® QuickFiller

Light weight filler for filling cracks and holes. Does not shrink, dries quickly.



DESCRIPTION

A lightweight filler for filling holes up to 10 mm, cracks, screw holes, and joints on many materials. Can be used on walls as well as ceilings.

USES

- Indoor use only!
- For filling holes and cracks on:
 - stucco
 - plaster decorations
 - concrete
 - plastered surfaces
 - wood

FEATURES

- Ultra lightweight
- Very little shrinkage
- Can be over-painted
- Sandable after curing
- Easy to apply and clean

CERTIFICATES AND TEST REPORTS

- EC1 & M1 for low emission

PRODUCT INFORMATION

Composition	Acrylic dispersion
Packaging	310 ml cartridge (12x310ml in box)
Shelf life	12 months from production date (s. packaging) in unopened packaging. Opened packaging should be closed immediately and used up as soon as possible.
Storage conditions	May not be exposed to temperatures below +5°C and above +25°C. The product withstands frost during transportation (Up to -15°C) but must be used at room temperature.
Appearance and colour	White paste
Density	0,57 kg/dm ³

TECHNICAL INFORMATION

Temperature resistance	From -20°C to +75°C
------------------------	---------------------

APPLICATION INFORMATION

Layer thickness	Filling capacity <10 mm
Ambient air temperature	From +5°C to +30°C (applies to environment and substrate)
Waiting time to overcoating	Overpaintable after fully dry
Waiting time	Can be grinded after 2 h drying time, at 23°C and 50% RH.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

NOTES ON INSTALLATION

- Not suitable for continuous exposure to water.
- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene, and bituminous substrates.

SURFACE PREPARATION

The surface must be dry, firm, and clean. Substrate to be cleared of all loose particles, porous substrates do not need to be dry.

APPLICATION

Apply the product with a gun and/or trowel. Can be overpainted with water-based paint when fully dry. A compatibility testing with paint prior to application is recommended.

CLEANING OF EQUIPMENT

Clean tools directly after use with warm water. If the product has dried, the product can be removed mechanically.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB
Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

PRODUCT DATA SHEET
Casco® QuickFiller
January 2024, Version 01.01
021840301000000012

CascoQuickFiller-en-SECASCO-(01-2024)-1-1.pdf