

PRODUCT DATA SHEET

Casco® WoodFiller

Solvent based wood filler developed for mending small damages on wood e.g. knots and cracks

DESCRIPTION

Solvent based wood filler developed for mending small damages on wood e.g. knots and cracks.

USES

Because of its excellent quality this wood filler is often applied on wooden floors.
The surface can be painted, lacquered, and stained.

CHARACTERISTICS / ADVANTAGES

- Indoor use
- Short drying time
- Has good filling action
- Has smooth finish

SUSTAINABILITY

For the product's assessment in the different building criteria systems, see [MiljöAppen](#).

Here you will also find information about EC1, M1, link to the building product declaration, safety data sheets etc. The MiljöAppen, can also be reached by entering www.sikamiljoapp.se in your web browser.

PRODUCT INFORMATION

Composition	Basis: Nitrocellulose and wood flower Solvent: Acetone, Ethylacetate, Iso-propyl alcohol
Packaging	Tin cont. 125 ml
Shelf life	12 months in closed package
Storage conditions	May not be exposed to temperature below +10 °C or above +30 °C
Density	~900 kg/m ³
Solid content by mass	Dry solids: ~40 %
Consistency	Pasty

APPLICATION INFORMATION

Relative air humidity	Moisture content: Of wood ~12 % and air ~65 %
Substrate temperature	Application temperature: +10 °C - +25 °C. Provide adequate ventilation.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

When working with adhesive, cleanliness must be observed. Therefore, always work carefully and systematically in order to avoid unnecessary spillage. Keep out of reach of children. Do not empty into drains.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

EQUIPMENT

Plain towel, painters knife, or similar tool.

APPLICATION

Application time: Do not apply more products that can be used within 5 minutes.
Dust free after 20-30 minutes.
Recoat-able after ~ 10 hours.

DIRECTIONS FOR USE

Casco® WoodFiller contains solvents to provide adequate ventilation.

Surfaces must be clean and dry. A roughening of the surface with fine sandpaper favorably affects adhesion.

Fill knots and cracks with some excess as the product will shrink during drying.

Deep defects must be filled several times, with drying in between.

Layers up to 3 mm can normally be sanded after 30 minutes to 1 hour (30 min in 50 % relative humidity).

For thicker layers it is advisable to fill in several layers. After sanding and cleaning the surface can be painted, lacquered, and stained like wood. When staining it is recommended to make a pre-test on a separate piece of wood

Casco® WoodFiller has limited resistance to moisture.

CLEANING OF EQUIPMENT

Tools are cleaned with water before the product is dried.

Cured wood filler must be removed mechanically. On skin, uncured wood filler is wiped off with a rag, then wash with soap and water.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB

Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu



PRODUCT DATA SHEET

Casco® WoodFiller
March 2023, Version 02.01
020813020010000021

CascoWoodFiller-en-SECASCO-(03-2023)-2-1.pdf