

PRODUCT DATA SHEET

Casco® Gipsplate filler

Light weight filler for filling holes and cracks on most materials.

DESCRIPTION

A lightweight filler for filling holes, cracks and joints on materials such as stucco, plaster decorations, concrete, plastered surfaces and wood. Can be used on walls as well as ceilings.

USES

For filling holes and cracks on:

- stucco
- plaster decorations
- concrete
- plastered surfaces
- wood.

Indoor use only!

CHARACTERISTICS / ADVANTAGES

- Very little shrinkage
- Can be over-painted after 10 min at 20°C
- Light weight technology

PRODUCT INFORMATION

Packaging	310 ml cartridge
Appearance / Colour	White
Shelf life	12 months in unopened package.
Storage conditions	Store at max temp of 25°C. The product can be frozen.
Density	0,57 kg/dm ³
Layer thickness	Filling capacity 10 mm.
Ambient air temperature	Working temperature shall not be below +5°C, best between +10°C to +20°C.
Substrate temperature	Substrate temperature shall not be below +5°C, best between +10°C to +20°C.
Drying time	Can be grinded after 2 h drying time, at 23°C and 50% RH.
Waiting time to overcoating	Can be over painted after 10 min drying, at +20°C.

APPLICATION INSTRUCTIONS

APPLICATION

The surface must be dry, firm and clean. Remove any loose surfacing mechanically.

Apply the product with gun and/or trowel.

Can be over painted with a waterbased paint.

CLEANING OF EQUIPMENT

Clean tools directly after use with warm water. If the product has dried, the product can be removed mechanically.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB

Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

PRODUCT DATA SHEET

Casco® Gipsplate filler
September 2020, Version 01.02
021840303000000020

CascoGipsplatefiller-en-SECASCO-(09-2020)-1-2.pdf