

PRODUCT DATA SHEET

Casco® NonWoven

Wall adhesive for nonwoven wallpaper.



DESCRIPTION

Wall adhesive for nonwoven wallpaper. Can be applied either directly on the wall or on the wallpaper. Easy to apply, minimal splashing, very high bonding strength.

USES

- For dry rooms
- For nonwoven wallpaper
- Suitable also for paper and glass-fiber wallpaper

CHARACTERISTICS / ADVANTAGES

- Apply with roller, brush, or wallpaper machine
- Minimal splashing
- High bonding strength
- Easy to apply

APPROVALS / CERTIFICATES

- Ec1 Plus & M1 for low emission

PRODUCT INFORMATION

Composition	Polyvinylacetat dispersion and starchderivat.
Packaging	15 L, 5 L, 1 L
Shelf life	12 months from production date (s. packaging) in an unopened bucket. Opened buckets should be closed immediately and used up as soon as possible.
Storage conditions	Store in dry and cool condition.
Colour	White / Transparent when dry
Density	1050 kg/m ³
Consistency	Thixotropic

APPLICATION INFORMATION

Consumption	ca 4 m ² /liter
Ambient air temperature	Not below +18°C in both the substrate and the material
Open Time	Ca 10 – 30 min. Application time is highly dependent on the amount of adhesive applied, the absorbency of the underlying surface, the temperature and the air humidity.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

Depending on the wall you have today, follow the guideline below. Always make sure to also follow the instructions from the wallpaper producer.

SUBSTRATE QUALITY

- Concrete, light concrete etc.: Needs to be full surface levelled before wall papering. See "Levelling".
- Levelled surfaces (strongly absorbent): Needs to be pre-glued with diluted wall adhesive before wall papering (mix 1 part adhesive with 1 part water), to prevent poor bonding and blisters of the wallpaper. Pre-glue the wall with diluted wall adhesive one day before wall papering. Small holes and cracks are filled with suitable filler, see "Levelling".
- Plasterboard, chipboard, and wood fiber boards: Do not need full surface levelling but small holes and cracks should be filled, see "Levelling".
- Painted walls: Wash the walls with a paint wash or the likewise. If there are holes / cracks they should be filled, see "Levelling".
- Wall with wallpaper: It is possible to wallpaper directly on old wallpaper, if there are no more than 5 layers provided, they are well attached and free of blisters. If the wallpaper has structure (fiberglass, sea grass etc.), the wall needs to be full surface levelled. For the best result, remove old wallpaper. See "Demolition" and "Levelling".
- Demolition of wallpaper: Vinyl wallpaper with paper backing and fiberglass coverings etc. are torn by "cleavage", meaning completely free from the wall. Other wallpaper is soaked with Casco® Remover and scratched with a steel trowel. Apply the Casco® Remover with a roller or sponge and let sit for approx. 30 min, then scrape off with a steel trowel.

SUBSTRATE PREPARATION

Levelling

- Remove any loose parts from the wall, as well as make sure it is dry and clean (brush or wipe the wall clean)
- Fill holes and cracks with small steel spatula, grind when dried.
- Check if you have larger bulges in the wall, use a leveler. If you have large bulges, they need to be levelled out.
- When levelling on structured wallpaper, make sure

to shave wallpaper edges.

- Large cracks and holes (more than 10 mm) on concrete etc. are filled with powder levelling compound
- On uneven walls, level twice, grind and clean the wall. On plain surfaces there is no need to level before wallpapering.
- Clean the wall with a brush or wet cloth
- On full surface levelled walls, pre-glue the walls with dilute wall adhesive (1:1) one day in advance of wall papering.
- Start wallpapering!

For full surface levelling, hold the trowel in an angle of approx. 30° to the wall. Make sure to not press too hard, to create edges. Apply the levelling compound with large strikes.

See list at the end for selection of wall levelling compound:

- Small holes/cracks: Casco® MultiFill (max 10mm), CascoSpack Medium (max 5mm) or CascoSpack S (max 2 mm)
- Large holes: Casco® OneFill Premium (up to 50 mm)
- For joints in gypsumboards etc: Casco® Gipsplate-Filler, Casco® MultiFill or CascoSpack Medium
- For full surface leveling: CascoSpack Medium or Casco® WallFiller
- For large holes/cracks in concrete etc: Casco® HusFix or Casco® HusFix Rapid

APPLICATION METHOD / TOOLS

Roller, brush or wallpaper machine.

APPLICATION

The first board

When you start wallpapering, start from a window and wallpaper to the darkest part of the room. In this way the joints will appear the least when the light falls on the walls.

To make sure you mount the wallpaper in level, draw a vertical line (use a leveler) a little less than the width of a board from the window. If you choose to start at a corner, draw the vertical line so that it is 1 cm past the corner, to create an overlap to the next wall and hence get a nice corner.

For most of the wallpaper, the adhesive is applied directly to the wall. (For paper wallpaper, apply the adhesive with a roller on the wallpaper, then swell for about 5-30 minutes before assembly). When applying the wall adhesive, work in the full height of the wall from the window and pass vertical line. Start gluing it at the bottom and work upwards on the wall. It is warmer under the roof, so the glue dries faster there. For easy mounting, in cases where the adhesive can be applied to the wall, use a trough, and pull the wallpaper to the ceiling so that it is 4-5 cm taller than the wall.

Make sure to press out all blisters/bubbles diagonal with a soft brush or a plastic trowel. For nice and sharp edges against sealing, lists, window frames etc.,

PRODUCT DATA SHEET

Casco® NonWoven

December 2022, Version 03.01

020513030000000035

use a sharp trowel to press the wallpaper into the corner, and cut off the excess wallpaper directly with a sharp knife. Hold the knife in approx. 45° to the wall for the best result.

Wash away glue residue from wallpaper etc. immediately with sponge and clean water. Replace water frequently.

The second board

Check if the wallpaper you selected should be mounted with overlap or edge to edge (see label on the wallpaper roll). Since you now have a board in level, it is just to continue applying glue and wallpaper as in previous steps. Note if your wallpaper has pattern that needs to be matching and note that even striped wallpaper should be mounted in the "same direction".

Around doors and windows

For easy application of the adhesive, use a brush along doors and window frames etc. Put up the wallpaper with an overlap to the list of 6-7 cm. Cut clean directly after mounting, use a sharp trowel and a sharp knife. In the corners of a window, cut diagonally for a nice result.

When you wallpaper in a corner of the room, make sure you have an overlap of the wallpaper, even if the wallpaper normally is mounted edge to edge. This is to be able to create a board in vertical level for the next wall, since corners seldom are fully in level. Make the overlap with at least 1 cm.

Power Plugs

Switch off the power when wallpapering at or around the circuit breaker and power outlet. Remove the protective cover and mount the wallpaper, let the board cover the contact. Cut a cross over the contact and cut away the four tabs with the excess wallpaper close to the connector. Then put back the protective cover before you continue.

CLEANING OF EQUIPMENT

Clean tools with water before the adhesive dries. Use methylated spirits to dissolve dry adhesive.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations

Sika Sverige AB
Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

CascoNonWoven-en-SECASCO-(12-2022)-3-1.pdf

PRODUCT DATA SHEET
Casco® NonWoven
December 2022, Version 03.01
020513030000000035