

PRODUCT DATA SHEET

Casco® Kontaktlim Förtunning

Solution of thinner to be used with solvent based contact adhesives.

DESCRIPTION

To be used for diluting contact adhesive, cleaning tools, removing glue stains, etc.

USES

To be used with solvent based contact adhesive when;

- Cleaning tools.
- Diluting the adhesive for spraying etc.
- Removing glue stains.

CHARACTERISTICS / ADVANTAGES

- Clear, transparent colour
- Not sensitive to frost.

PRODUCT INFORMATION

Packaging	1 L
Shelf life	36 months in sealed packaging.
Storage conditions	Store in a cool, frost-free place. Max temp +25°C
Colour	Transparent
Density	Approx. 758 kg/m ³
Volatile organic compound (VOC) content	Heptane and ethyl acetate.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

Highly flammable, avoid open flames and sparks. Hazardous on inhalation, skin contact and ingestion, use suitable gloves and goggles. Store out of the reach of children. Store well away from sources of ignition. No smoking. Good ventilation is essential. Do not dispose of in public drains. Take measures to guard against static electricity. Contains toluene and heptanes.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) con-

taining physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

Diluting adhesive

When diluting Contact Adhesive S9 Super for spraying, use 10–14% KontaktlimFörtunning (Contact Adhesive Thinner).

Cleaning

For cleaning, use non-diluted product.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB

Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

PRODUCT DATA SHEET

Casco® Kontaktlim Förtunning
January 2023, Version 01.01
020516020000000050

CascoKontaktlimFrtunning-en-SECASCO-(01-2023)-1-1.pdf