

PRODUCT DATA SHEET

CascoSpack S

QUICK-DRYING FILLER FOR JOINERY.



DESCRIPTION

A ready-mixed, quick-drying latex filler for joinery. For filling holes and broad filling of small surfaces up to 2mm. Very good bonding to most construction materials.

USES

- For indoor use in dry rooms
- Filling of holes and broad filling of small surfaces

CHARACTERISTICS / ADVANTAGES

- Quick-drying
- Easy to sand
- Good bond to most materials
- White

APPROVALS / CERTIFICATES

- M1 emission classification
- CE -marking according to EN 15824

PRODUCT INFORMATION

| | |
|-----------------------|--|
| Composition | Dispersionbased filler |
| Packaging | 400 ml |
| Shelf life | 12 months from production date (s. packaging) in an unopened packaging. Opened packaging should be closed immediately and used up as soon as possible. |
| Storage conditions | In cool, dry, and frost-free conditions (in closed packaging), + 5°C to + 20°C |
| Appearance and colour | White paste |
| Maximum grain size | 0,02 mm |
| Density | 1,75 kg/l. |

APPLICATION INFORMATION

| | |
|-----------------------------|--|
| Consumption | approx. 1litre/mm/m ² depending on surface. |
| Layer thickness | up to 2 mm |
| Ambient air temperature | +5°C ... +35°C |
| Curing time | 2-4 hours/ layer (+23°C/ 50% RF) |
| Waiting time to overcoating | approx. 1-2 hour, when dry. |

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

- The product can be used on most construction materials for small repairs (up to 2 mm).
- The product can be overpainted or be used as underlay for wallpaper.

MIXING

No mixing, ready-to-use.

APPLICATION

- Before you start levelling, make sure the surfaces are clean, dry, and free from loose particles.
- Use a steel trowel and hold the trowel in an angle of approx. 30° to the wall. Do not press too hard and apply the levelling compound with large strokes.
- Wooden surfaces have to be covered with a primer first.
- Even out any irregularities with filler. Leave to dry and then sand the surface smooth until it is even.
- Drying time is affected by layer thickness, temperature, humidity, substrate, etc..
- Add filler several times in order to minimize sanding process between every layer.
- When applying a second layer, make sure that the filler has dried before starting sanding.
- Make sure to also clean the wall with a dry brush or cloth before applying the next layer of levelling compound, wallpaper, or paint.
- Dust-free surface can be overpainted with latex/ acrylic paint.
- If wallpaper is applied to the wall, make sure to pre-glue the wall with diluted wallpaper adhesive (follow the wallpaper and adhesive manufacturer's recommendations), to secure a good bond and to reduce the risk of blisters.

APPLICATION METHOD / TOOLS

Steel spatula/trowel or putty knife

CLEANING OF EQUIPMENT

Clean used tools with water after use.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB

Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

PRODUCT DATA SHEET

CascoSpack S
January 2023, Version 02.02
021840303000000019

CascoSpackS-en-SECASCO-(01-2023)-2-2.pdf