

PRODUCT DATA SHEET

CascoSpack LV

WALL-LEVELLING COMPOUND FOR WET ROOMS WITH HIGH FILLING CAPACITY.



DESCRIPTION

A ready-mixed wall levelling compound up to 5mm with extra fine surface and high filling capacity. Suitable for use in wet rooms. CascoSpack LV is very easy to apply and has low shrinkage. Suitable for full surface levelling and small repairs on plaster, concrete, aerated concrete etc. Ideal for applying joint tape.

USES

- For wet and dry room indoors
- For full surface levelling or small repairs

CHARACTERISTICS / ADVANTAGES

- Short drying time
- Extremely easy to apply
- Very fine grain with excellent filling capacity
- Very smooth surface
- Easy to sand

APPROVALS / CERTIFICATES

- M1 emission classification
- CE-marking according to EN 15824 and EN 13963

PRODUCT INFORMATION

Composition	Water-resistant filler based on calcium carbonate and acrylic copolymer
Packaging	10 litres
Shelf life	12 months from production date (s. packaging) in an unopened packaging. Opened packaging should be closed immediately and used up as soon as possible
Storage conditions	In cool, dry, and frost-free conditions (in closed packaging), + 5°C to + 20°C
Appearance and colour	Light blue paste
Density	1,2 kg/l

APPLICATION INFORMATION

Consumption	1 litre/m ² /mm
Layer thickness	Up to 5 mm
Ambient air temperature	+10°C ... +30°C, but not below +5°C
Curing time	1-2 hours/ 1mm (+23°C/ 50% RF). Drying time may vary depending on the layer thickness, substrate, temperature, humidity, etc.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

- The product can be used on material such as gypsum boards, concrete, aerated concrete etc. for small repairs (up to 5 mm) and for full surface levelling.
- Holes deeper than 5 mm need to be filled several times, with sufficient drying time between applications.
- The product can be overpainted with latex/alkyd paint or be used as underlay for PVC wall coverings, membrane or tiles.

MIXING

Ready-to-use.

APPLICATION

- Before you start levelling, make sure the surfaces are clean, dry, and free from loose particles.
- Use a steel trowel and hold the trowel in an angle of approx. 30° to the wall. Do not press too hard and apply the levelling compound with large strokes.
- Even out any irregularities with filler.
- Leave to dry and then sand the surface smooth until it is even.
- After each levelling, sand the surface with a fine sandpaper once the filler has dried.
- Add filler several times in order to minimize sanding process between every layer. When applying a second layer, make sure that the filler has dried before starting sanding.
- Make sure to also clean the wall with a dry brush or cloth before applying the next layer of levelling compound, wall covering, membrane, tile, or paint.
- Dust-free surface can be overpainted with latex/ acrylic paint or covered by elastic wall covering, membrane or tiles.

- If a wall cover is applied to the wall, make sure to pre-glue the wall with diluted wall adhesive (see label of wall adhesive for instructions how to dilute), to secure a good bond and to reduce the risk of blisters.
- For large cracks/holes, use HusFix or HusFix Rapid.

APPLICATION METHOD / TOOLS

Steel spatula

CLEANING OF EQUIPMENT

Clean used tools with water after use.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB

Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

PRODUCT DATA SHEET

CascoSpack LV
January 2023, Version 04.01
021840103000000017

CascoSpackLV-en-SECASCO-(01-2023)-4-1.pdf