

PRODUCT DATA SHEET

CascoSpack Medium

MEDIUM-COARSE WALL LEVELLING COMPOUND WITH HIGH FILLING CAPACITY.



DESCRIPTION

A ready mixed, easy to sand, medium-grained wall filler with a filling capacity of up to 4 mm layer thickness.

CascoSpack Medium is suitable for full surface levelling, small repairs, filling joints and for joint tape. It has good adhesion to plaster, concrete, particle boards and gypsum boards. The walls can be painted or covered with wallpaper.

USES

- For indoor use in dry rooms
- Full surface levelling or small repairs
- Underlay for wallpaper

FEATURES

- High filling capacity
- Easy to sand
- Overpaintable
- Easy to apply
- Ready-mixed

CERTIFICATES AND TEST REPORTS

- M1 emission classification
- CE -marking according to EN 15824 and EN 13963.

PRODUCT INFORMATION

Composition	Pasty copolymer
Packaging	5 liters and 400 ml
Shelf life	12 months from production date (s. packaging) in an unopened packaging. Opened packaging should be closed immediately and used up as soon as possible.
Storage conditions	In cool, dry, and frost-free conditions (in closed packaging), + 5°C to + 20°C
Appearance and colour	Light grey paste
Maximum grain size	0,2 mm
Density	1,2 kg/m ³

APPLICATION INFORMATION

Consumption	1litre / m ² / mm
Layer thickness	Up to 4 mm

Ambient air temperature	+10°C ... +35°C, not below +5°C
Curing time	1 hour/ mm (+23°C/ 50% RF). Drying time may vary depending on the layer thickness, substrate, temperature, humidity, etc.
Waiting time to overcoating	24 hours

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

- The product can be used on material such as gypsum boards, wood, concrete, light concrete, particle board etc. for small repairs (up to 4 mm) and for full surface levelling
- Holes deeper than 4 mm need to be filled several times, with sufficient drying time between applications.
- The product can be over painted or be used as underlay for wallpaper.

MIXING

Ready-to-use.

APPLICATION

- Before you start levelling, make sure the surfaces are clean, dry, and free from loose particles.
- Use a steel trowel and hold the trowel in an angle of approx. 30° to the wall. Do not press too hard and apply the levelling compound with large strokes.
- When applying a second layer, make sure to sand the surface with a fine sandpaper once the filler has dried.
- Drying time is affected by layer thickness, temperature, humidity, substrate, etc..
- Make sure to also clean the wall with a dry brush or cloth before applying the next layer of levelling compound, wallpaper, or paint.

- If wallpaper is applied to the wall, make sure to pre-glue the wall with diluted wallpaper adhesive (follow the wallpaper and adhesive manufacturer's recommendations), to secure a good bond and to reduce the risk of blisters.

APPLICATION METHOD / TOOLS

Steel spatula

CLEANING OF EQUIPMENT

Clean used tools with water after use.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB
Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

PRODUCT DATA SHEET
CascoSpack Medium
January 2024, Version 03.01
021840303000000046

CascoSpackMedium-en-SECASCO-(01-2024)-3-1.pdf