

## PRODUCT DATA SHEET

# Casco® VD Ready Fix

Fast curing special primer for absorbent substrates, ready to use.



### DESCRIPTION

Ready to use solvent-free synthetic resin dispersion primer, especially for protection against moisture in the levelling compounds. Also, for reducing absorbency and increasing adhesion of the levelling compound.

### USES

- For indoor use only.
- For floor and wall
- Suitable for substrates with underfloor heating

### CHARACTERISTICS / ADVANTAGES

- Solvent free /Water based
- Ready mixed
- Quick drying time
- Good adhesion to the absorbent substrates
- Easy application with roller

### APPROVALS / CERTIFICATES

- EC1 Plus
- M1

### PRODUCT INFORMATION

Composition	Synthetic resin dispersion, solvent free
Packaging	5 kg canister
Shelf life	12 months in an unopened package. Opened package should be closed immediately and used up as soon as possible.
Storage conditions	In cool, dry, frost-free conditions, not below + 5 °C.
Colour	Purple
Density	1,00 kg/l
Solid content by volume	approx. 22%
pH-Value	approx. 8,0

### APPLICATION INFORMATION

Mixing ratio	Ready to use
Yield	7-10 m <sup>2</sup> / kg (100-150g/m <sup>2</sup> ), depending on the type and absorbency of the substrate and applicator device
Ambient air temperature	+5°C to +30°C, (subfloor not below +5°C)

- Adhesion improvement and absorption reduction approx. 10 minutes
- As moisture protection approx. 1 hour

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

Casco® VD Ready Fix can be used as a primer for reducing absorbency, to improve adhesion for levelling compounds on absorbent substrates and to protect against moisture in levelling compounds during the application phase. For non-absorbent surfaces, Casco® VD Super Grip is recommended.

### EQUIPMENT

Brush or roller.

### SUBSTRATE QUALITY

Casco® VD Ready Fix is suitable for:

- concrete
- aerated concrete
- cement and rapid cement screeds
- calcium sulphate-based screeds
- gypsum plaster (according to EN 13279-1)
- cement plaster, lime-cement plaster (CS I - CS IV according to EN 998-1)
- old substrates with old water-resistant adhesive residues
- gypsum board
- wooden substrates.

### REQUIREMENTS OF SUBSTRATE

- Adequate strength, bearing strength, dimensional stability, and permanent dryness.
- Free of layers which reduce adhesion, e.g., dust, dirt, oil, fat, wax cleaning agents and loose particles.
- Layers of water-soluble adhesives, e.g., sulphatic adhesives, should be removed completely.
- Old water-resistant adhesives should be mechanically removed as thoroughly as possible.
- Rooms that do not have a cellar underneath must be sealed against rising dampness in compliance with the standard.
- The requirements of the relevant valid standards, guidelines and data sheets apply.

Sika Sverige AB

### SUBSTRATE PREPARATION

Box 8061

Mechanically remove areas of loose surfacing, pollutants, and cement skin, if any. Vacuum clean the surface. The underlying surface must be firm, clean, and dust-free before priming.



### PRODUCT DATA SHEET

Casco® VD Ready Fix

January 2023, Version 03.01

02179040000000038

## MIXING

Do not mix Casco® VD Ready Fix with water.

## APPLICATION

Recommended method of working:

- Stir the primer before use.
- Apply primer evenly on the dry substrate with a brush so that the primer penetrates the substrate efficiently. Puddles must be avoided.
- Levelling compounds can be applied after drying time approx. 10 minutes to 1 hour. Refer to the product data sheets for the appropriate levelling compounds.

Note! If the primed surface is older than 72 hours (3d) before applying the leveling compound, the priming needs to be repeated.

## CLEANING OF EQUIPMENT

Clean tools immediately with water. Use acetone to remove dried primer.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website [www.casco.eu](http://www.casco.eu).

CascoVDReadyFix-en-SECASCO-(01-2023)-3-1.pdf