

Casco[®]FloorSeal Golvfog+

PRESTANDEDEKLARATION No. 13284131

1	PRODUKTTYPENS UNIKA IDENTIFIKATIONSKOD:	13284131
2	AVSEDD ANVÄNDNING/AVSEDDA ANVÄNDNINGAR:	EN 15651-4:2012 Fogmassa för gångtrafikerade ytor PW INT
3	TILLVERKARE:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	TILLVERKARENS REPRESENTANT:	
5	SYSTEM FÖR BEDÖMNING OCH FORTLÖPANDE KONTROLL AV PRESTANDA:	System 3 System 3 för brandklass
6a	HARMONISERAD STANDARD:	EN 15651-4:2012
	Anmält/anmälda organ:	1213

Declaration of Performance

Casco[®]FloorSeal Golvfog+

13284131

2024.04 , ver. 1

1001

7 ANGIVEN PRESTANDA

Väsentliga egenskaper	Prestanda	AVCP	Harmoniserad teknisk specifikation
Brandklass	Klass E	System 3	EN 15651-4:2012
Utsläpp av miljö- och hälsofarliga kemikalier	NPD		
Vatten- och lufttät			
Hållfasthetsegenskaper vid bibehållen utsträckning	NF vid 60% elongation	System 3	
Volymförlust	≤ 10%	System 3	
Rivmotstånd	NF vid 50% elongation	System 3	
Hållbarhet	Godkänd	System 3	


8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Daniel Jonsson
Function: General Manager
At Spånga on 15 April 2024

Name: Marie Rönn
Function: Product Manager
At Spånga on 15 April 2024



End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Casco® FloorSeal Golvfog+	EN 15651-3:2012	40913950
Casco® FloorSeal Golvfog+	EN 15651-1:2012	29079597

Declaration of Performance

Casco® FloorSeal Golvfog+
13284131
2024.04 , ver. 1
1001



14

Sika Services AG, Zurich, Switzerland

DoP No. 13284131

EN 15651-4:2012

Notified Body 1213

Fogmassa för gångtrafikerade ytor PW INT

Brandklass	Klass E	System 3
Vatten – och lufttät		
Hållfasthetsegenskaper vid bibehållen utsträckning	NF vid 60% elongation	System 3
Volymförlust	≤ 10%	System 3
Rivmotstånd	NF vid 50% elongation	System 3
Hållbarhet	Godkänd	System 3

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Casco®FloorSeal Golvfog+

13284131

2024.04 , ver. 1

1001

3/4

BUILDING TRUST



Sika Sweden
Domnarvsvägen 15
163 53 Spånga
Sweden
www.sika.se

Declaration of Performance
Casco®FloorSeal Golvfog+
13284131
2024.04 , ver. 1
1001

