


PRODUCT DATA SHEET

CascoPlomb

ADHESIVE FOR SEALING OF THE JOINT BETWEEN PVC COVERING AND THE WALL.



DESCRIPTION

Adhesive for sealing of the joint between PVC covering and the wall. Specially developed adhesive for sealing of the edge between the folded floor covering to the wall, and the wall. Recommended where there are high hygienically demands, like in hospitals etc.

USES

- Sealing of edge between the folded floor covering to the wall, and the wall.
- For high hygienically demands (hospitals etc).

CHARACTERISTICS / ADVANTAGES

- For sealing of joints.
- In areas with high hygienically demands

PRODUCT INFORMATION

Composition	Copolymer dispersion
Packaging	300 ml bottle
Colour	White coloured when wet, becomes transparent when cured.
Shelf life	1 year in closed containers
Storage conditions	Should not be exposed to temperatures below 0 °C and above +30 °C. Opened containers should be closed immediately.
Density	Appr. 1040 kg/m ³
Solid content by weight	Appr. 40 %
Viscosity	Appr. 100 000 mPa.s, Brookfield LVT, sp 6, 20 rpm, 20 °C.

APPLICATION INFORMATION

Consumption	0,3 liter to approx. 50 meter joint.
Ambient Air Temperature	Between +18 °C and +25 °C
Relative Air Humidity	20–70 % RH.
Curing Time	Within 24 hours the adhesive has created a transparent sealing.

APPLICATION INSTRUCTIONS

Cut of the tip of the bottle. Apply a thick string of adhesive to fill out unevenness. Within 24 hours the adhesive has created a transparent sealing of the edge between the folded floor covering and the wall.

SUBSTRATE PREPARATION

Before applying the adhesive make sure that the surface is clean and dust free.

CLEANING OF EQUIPMENT

Clean application tools with water before the adhesive has dried. Dried adhesive is dissolved in ethanol.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

In case of skin contact, wash with soap and water. In case of eye contact, rinse thoroughly with water. For further information, see Safety Data Sheet.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB
Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

PRODUCT DATA SHEET
CascoPlomb
March 2020, Version 01.01
020512030110000016

CascoPlomb-en-SECASCO-(03-2020)-1-1.pdf