

PRODUCT DATA SHEET

Casco® MultiFill

WALL FILLER FOR REPAIRS UP TO 10 MM.

DESCRIPTION

A ready-mixed, acrylic-based fine filler for repairs up to 10 mm. Casco® MultiFill does not shrink or crack and can be used on most materials such as: wood, brick, concrete, metal, masonite and fiberboard. Not for PVC or aluminum.

CHARACTERISTICS / ADVANTAGES

- Easy to sand
- No shrinkage
- No cracks
- White

USES

- For indoor and outdoor use (over painted).
- Repairs up to 10 mm

PRODUCT INFORMATION

Composition	Water-resistant filler based on calcium carbonate and acrylic copolymer
Packaging	250 ml
Shelf life	12 months from production date (s. packaging) in an unopened packaging. Opened packaging should be closed immediately and used up as soon as possible.
Storage conditions	In cool, dry, and frost-free conditions (in closed packaging), + 5°C to + 20°C
Appearance and colour	White paste
Density	approx. 1,7 kg/l

APPLICATION INFORMATION

Layer thickness	up to 10 mm/layer
Ambient air temperature	+10°C ... +25°C, but not below +5°C
Curing time	1 hour/ 2mm (+23°C/ 50% RF). Drying time may vary depending on the layer thickness, substrate, temperature, humidity, etc.
Waiting time to overcoating	approx. 0,5-1 hour /mm layer thickness.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

- The product can be used on most construction materials for small repairs (up to 10 mm). Not for PVC or aluminium.
- The product can be overpainted or be used as underlay for wallpaper.

MIXING

No mixing, ready-to-use.

APPLICATION

- Before you start levelling, make sure the surfaces are clean, dry, and free from loose particles.
- Use a steel trowel and hold the trowel in an angle of approx. 30° to the wall. Do not press too hard and apply the levelling compound with large strokes.
- Knead the tube thoroughly before use.
- Holes deeper than 10 mm need to be filled several times, with sufficient drying time between applications.
- When repairing large holes and cracks, use Casco OneFill Premium and then finish with Casco® Multi-Fill.
- Seal the tube tightly after use.
- For outdoor use, the filler needs to be over painted
- NOTE! Do not use on PVC or aluminium.

APPLICATION METHOD / TOOLS

Steel spatula/trowel or putty knife.

CLEANING OF EQUIPMENT

Clean used tools with water after use.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Casco products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or on the website www.casco.eu.

Sika Sverige AB
Domnarvsgatan 15
Box 8061
SE- 163 08 Spånga Sweden
TEL: +46 8 621 89 00
info@se.sika.com
www.casco.eu

PRODUCT DATA SHEET
Casco® MultiFill
January 2023, Version 02.01
021840303000000025

CascoMultiFill-en-SECASCO-(01-2023)-2-1.pdf